

Pipe Range Extender



The Pipe Range Extender can be used to improve Sensor wireless performance when measuring temperature on pipes. The sensing element is thermally coupled to the pipe using a thermal pad to ensure a good measurement.

Features

- Improves indoor range by up to 4X when mounted on metal pipes.
- Gives good thermal coupling between sensor and metal pipe
- Simple and robust installation on pipes

Specifications

Operating Conditions	
Temperature range ⁽¹⁾	-40 to 85 °C / -40 to 185 °F
Humidity at 25 °C / 77 °F	0 to 100% relative humidity
Recommended Storage Conditions	Cool and dry, near normal room temperature
Thermal conductivity of thermal pad	1.2W/m·K
Materials	ABS PA-757 T-flex™ 300
Typical Dimensions ⁽²⁾	36.7 x 30.1 x 29.3 mm (±0.2 mm)
Typical Weight ⁽²⁾	15.2 g (±0.5 g)
Certifications and Compliance	Sensor with Range Extender, certified to FCC and ISED regulations FCC ID: 2ATFX-100644 IC: 25087-100644 CE, WEEE

Footnotes

- (1): Maximum temperature range for the materials are -40 to 160 °C / -40 to 320 °F
(2): With thermal pad, without sensor

Disclaimer: The right is reserved to make changes at any time. Disruptive Technologies Research AS, including its affiliates, agents, employees, and all persons acting on its or their behalf, disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product. All parameters in datasheet are expected performance and not guaranteed min or max performance.

