


Superior product line

DoorProtect S Jeweller

Wireless opening detector.



What's new

Baseline DoorProtect Jeweller	Superior DoorProtect S Jeweller
1 reed switch	2 reed switches
SmartBracket mounting panel without holding screw	SmartBracket mounting panel with holding screw
Common battery	Enhanced battery
Glossy enclosure	Matte enclosure
Available for all PROs	Available only for accredited partners

This is the device of the **Superior product line**. Superior products are advanced versions of Jeweller devices. This product line is developed for projects. Only accredited Ajax Systems partners can sell, install, and administer Superior products.

Reliable opening detection

- Plastic reed switches: more durable than the glass ones
- Installing magnet on both sides of DoorProtect S: on the right or left
- Equipped with two magnets: small and big

Additional features


- Connector for a third-party detector with NC (normally closed) contact
- Chime function: Ajax sirens make a special sound when the door is opening

Jeweller communication technology

- Radio communication at a distance of up to 1,200 m in an open space
- Encryption and device authentication to prevent spoofing
- Regular polling to display the current statuses of the devices

Flawless autonomy


- Up to 5 years of battery life
- Low battery notifications
- Panasonic pre-installed battery



Quick installation and setup

- Pairing with a hub via QR code
- Remote control and configuration in the app
- Effortless installation and replacement

Intended certifications EN 50131 (Grade 2) PD 6662:2017 INCERT NFA2P SSF	Compatibility Hubs Hub Plus, Hub 2 (2G), Hub 2 (4G), Hub 2 Plus, Hub Hybrid (2G), Hub Hybrid (4G) Range extenders ReX, ReX 2	Communication with control panel Jeweller communication technology Frequency bands 868,0 – 868,6 MHz Communication range up to 1,200 m In an open space	Detection Sensitive elements 2 × reed switch Sensors' resource 2,000,000 openings Third-party detector connection detector with the normally closed (NC) contact type
Power supply Battery 1 × CR123A Battery life up to 5 years Manufacturer Panasonic	Installation Operating temperature range from -10°C to +40°C Operating humidity up to 75% Protection class IP50	Enclosure Colour white, black Dimensions 103 × 22 × 21 mm Weight 37 g	Complete set DoorProtect S Jeweller 2 magnets (small and big) 1 × CR123A battery (pre-installed) SmartBracket with holding screw Installation kit Outside-mounted terminal clamp Quick start guide



For detailed information, scan the QR code or follow the link:
ajax.systems/support/devices/doorprotect-s/

- ✉ support@ajax.systems
- 📍 @AjaxSystemsSupport_Bot
- 🌐 ajax.systems