





Density® Basic

A new « entry level » fog generator for home and shop target. The Density® Basic fog generator is the key to secure your valuables and permits by instantly repelling intruders. It is a fog system with a small size and high performances. Low power consumption. Plastic cover maximize performances for wireless connections.



JUST
3,8 KG


FEATURES



To protect premises from 5 to 45 m².



Fast and dense, this fog generator produce 135 m³ in 50 seconds.



COMPATIBILITY



ActiveCloud board for secure connection (2x128bits encryption) wired or WiFi.



API available for software and hardware customisation.

GENERAL SPECIFICATIONS

Weight	3,8 kg
Dimensions	325 mm x 265 mm x 115 mm
Color	White
Front cover	Plastic material
Operating time without mains power	1 hour
Heating time	Around 20 minutes
Energy consumption	Around 30 W

FOG GENERATOR

Suggested square meters up to	45 m ²
Max fog emitted in single shot	135 m ³ (EN standard) - commercial 390 m ³
Maximum shooting time	50 sec.
Max fog emitted with full fog bag	2340 m ³
N. of shots with max shooting	6
Pump	Yes
Fog tank capacity	500 ml
Horizontal mounting	Yes with opzional kit
Shooting time programmable	Yes
Backup battery	1,2 Ah 12V

INPUTS / OUTPUTS

Electronic board	2 inputs / 3 ouputs
------------------	---------------------

COMMUNICATION

Serial bus with standard protocol	Yes 2 serial
IP card ActiveCloud	Yes (optional)
Access to ActiveCloud	Yes (free)
Availability of Development APIs	Yes
WiFi	Yes (optional antenna)

Accessories for **Density® Basic**

Orientable wall bracket
Desk stand
Active Cloud LAN / Wi-Fi board
Active Server LAN / Wi-Fi board
Wi-Fi antenna for Lan board
Mounting kit Active Cloud/Active Server
Kit for horizontal mounting (side extra riser + fluid bag holder)

Density® refills

Fluid bag 500 ml **Density® Basic**

Optional configuration

Demo kit