

# Density®2400 Lite

The easy installation fog generator, dedicated to the protection of premises up to 270m². The Density® 2400 Lite fog generator is the key to secure your valuables and permises by instantly repelling intruders.













#### FEATURES



To protect premises from 5 to 270 m<sup>2</sup>.



Fast and dense, this fog generator produce 800 m<sup>3</sup> in 64 seconds.



#### — COMPATIBILITY



ActiveCloud board for secure connection (2x128bits encryption) wired or WiFi.



API available for software and hardware customisation.



Multidirectional nozzle adaptative to fit all installations types.

# **Density 2400** Lite technical specifications

### GENERAL SPECIFICATIONS

Weight	9,5 kg
Dimensions	390 mm x 300 mm x 130mm
Colors	White or black
Operating time without mains power	Over 1 hour
Heating time	Around 2 hours
Average power consumption after heat-up	48W
Vertical mounting	Yes
Horizontal mounting	Yes
Usb port for computer monitoring (Windows and Linux)	Yes
Adjustable nozzle	Yes
Nozzle extention	Yes (optional)

### FOG GENERATOR

64 seconds		
800 m³ (EN standard) - commercial 2400 m³		
Programmable in seconds		
1 L		
2		
Arming and shooting		
Empty bag, Shoot confirm and system failure		
Yes (optional)		
Yes (optional)		
Yes, 2		

## **ELECTRICAL SPECIFICATIONS**

Accessories for **Density® 2400** Lite

Orientable wall bracket

Desk stand

Mains power	230 V AC or 120 V AC
Average consumption	48 W
Heater max power in start	280 W
Backup battery 12V/2Ah	Not included

Active Cloud LAN / Wi-Fi board
Active Server LAN / Wi-Fi board
Wi-Fi antenna for Lan board
Mounting kit Active Cloud/Active Server / Serial relay board for Density Lite
Nozzle extention 5 cm
Nozzle extention 10 cm
Serial 4 relay board for Density® Lite (mounting kit not included)

Fluid bag 1000 ml **Density® 2400 Lite** 

### **Optional configurations**

**Density®** refills

Reverse shoot machine
Black painted cabinets
Demo kit