

Density 900 Lite

The easy installation fog generator, dedicated to the protection of premises up to 100m². The Density® 900 Lite fog generator is the key to secure your valuables and permises by instantly repelling intruders.

















To protect premises from 5 to 100 m².



Fast and dense, this fog generator produce 300 m³ in 40 seconds.



— COMPATIBILITY



ActiveCloud board for secure connection (2x128bits encryption) wired or WiFi.



API available for software and hardware customisation.



Multidirectional nozzle adaptative to fit all installations types.

Density 900 Lite technical specifications

GENERAL SPECIFICATIONS

8 kg	
390 mm x 300 mm x 130mm	
White or black	
Over 1 hour	
Around 1 hour	
37W	
Yes	
Yes	
Yes	
Yes	
Yes (optional)	

FOG GENERATOR

Single shoot max time	40 seconds	
Single shoot max fog output	300 m³ (EN standard) - commercial 900 m³	
Shot characteristics	Programmable in seconds	
Fluid container system	1 L	
Number of full Fog releases on a full fluid bag	5	
2 cabled inputs:	Arming and shooting	
3 cabled outputs:	Empty bag, Shoot confirm and system failure	
Top internal riser for optional boards	Yes (optional)	
Side internal riser for optional boards	Yes (optional)	
RS232 Serial ports for dedicated option boards	Yes, 2	
	· · · · · · · · · · · · · · · · · · ·	

ELECTRICAL SPECIFICATIONS

Mains power	230 V AC or 120 V AC
Average consumption	37 W
Heater max power in start	350 W
Backup battery 12V/2Ah	Not included

Accessories for Density® 900 Lite			
Active Cloud LAN / Wi-Fi board			
Active Server LAN / Wi-Fi board			
Wi-Fi antenna for Lan board			
Mounting kit Active Cloud/Active Server / Serial relay board for Density Lite			
Nozzle extention 5 cm			
Nozzle extention 10 cm			
Serial 4 relay board for Density® Lite (mounting kit not included)			
Orientable wall bracket			
Desk stand			

Den	sitv	r® r∈	fills
-----	------	-------	-------

Fluid bag 1000 ml **Density® 900 Lite**

Optional configurations

Reverse shoot machine
Black painted cabinets
Demo kit